



Open Networking Testing Service

Open Network Systems Interoperability Test Report

UNH-IOL — 21 Madbury Road, Suite 100 — Durham, NH 03824 — +1-603-862-0090

Carly Sun
10Gtek Transceivers Co. Ltd
info@10gtek.com

July 5, 2018

Enclosed are the results from the Open Network Systems Interoperability performed on:

Module or Cable Assembly Under Test (MUT/CUT):

Vendor and Device Type	10Gtek SFP+
Part Number	CAB-10GSFP-P3M

Host Under Test (HUT):

Host System 1 Composition	
Network Operating System	Cumulus
OS Version	3.4
Bare Metal Switch	Edge-Core 5712
Part Number	5712
ONIE Version	2018.02

This testing pertains to the Open Network Systems Interoperability Test Plan, which outlines a series of tests performed on a variety of optical transceivers and cables with bare-metal open switches running Network Operating Systems from multiple vendors. The focus of these tests was basic interoperability, which aims to validate the operation of open network systems.

As always, we welcome any comments regarding this Test Suite. If you have any questions about the test procedures or results, please feel free to contact me via e-mail at david@iol.unh.edu or by phone at +1-603-862-0090.

Regards,
David Woolf

Digital Signature Information

This document was created using an Adobe digital signature. A digital signature helps to ensure the authenticity of the document, but only in this digital format. For information on how to verify this document's integrity proceed to the following site:

<https://www.iol.unh.edu/testing/reports/certificate-install>

If the document status still indicates "Validity of author NOT confirmed", then please contact the UNH-IOL to confirm the document's authenticity. To further validate the certificate integrity, Adobe 6.0 should report the following fingerprint information:

MD5 Fingerprint: 80 60 3C EA 42 D6 61 38 62 24 14 6A 1F 66 E9 84

SHA-1 Fingerprint: 81 FF 90 E8 56 CB 95 7F 3E D6 4D B8 B2 99 EF BE 3C CC 7D DE



In section 2, the following equipment was used:

Test System Hardware	
EEPROM Reader	I2C Elite Reader

In section 3, the following equipment was used:

Test System Hardware	
Network Analyzer	PNA –Performance Network Analyzer

In section 4, the following equipment was used:

Test System Hardware	
Wide Bandwidth Oscilloscope	Keysight DCA-X 86100D Wide Bandwidth Oscilloscope
Waveform Analyzer	Keysight 86105C Optical Waveform Analyzer
50GHz Waveform Analyzer	Keysight 86108B Mega Module, 50GHz Bandwidth Waveform Analyzer
Clock Recovery Module	Keysight 83496B Optical/Electrical Clock Data Recovery Unit
High Performance Serial BERT	Tektronix BERTScope
Signal Quality Analyzer	BERTScope PRBS9 at 10.3125Gbps
De-Emphasis Signal Converter	Agilent N4916B

*Two modules used during testing

In section 6, an MLNK NICS was used to generate test traffic:

Test System Hardware	
Ethernet Traffic Generator	MLNK NICS
Software Version	Ostinato
Port Types	10G SFP

The following table contains possible results and their meanings.

Result	Interpretation
PASS	The Device Under Test (DUT) was observed to exhibit conformant behavior.
PASS W/ Comments	The specified behavior is demonstrated by the DUT; however this result indicates that either changes were made to the standard test procedure or results other than the expected results were observed.
FAIL	The DUT was observed to exhibit non-compliant behavior.
INFO	This Test is designed for informational purposes only. While the results may help ensure the interoperability of the DUT, a PASS/FAIL is not given for this test.
WARN	The DUT was observed to exhibit behavior that is not recommended.
N/A	Not Applicable. This test is not applicable for the DUT.
N/S	Not Supported. This test was not run due to features not implemented on the DUT.
N/T	Not tested. This test was not run.

Summary of Results- Conformance	
Test	Result
Test 1.1:	N/A
Test 1.2:	PASS
Test 3.1.1: Return Loss for 10G Passive Cable	PASS
Test 3.1.2: Insertion Loss for 10G Passive Cable	PASS
Test 5.1.1: Output Rise and Fall Times for 100G Host	PASS
Test 5.1.2: Transmitter Eye Mask for 100G Host	PASS
Test 5.1.3: Total Jitter for 100G Host	PASS
Test 5.1.4: Input and Output Return Loss on 100G Host	PASS

Summary of Results - Interoperability	
Test	Result
Test 2.1: Physical Compatibility with Supporting Devices	PASS
Test 2.2: Host Management of Module or Cable Assembly	PASS
Test 2.3: Diagnostic Optical Monitor Support	PASS
Test 6.1: Establish Baseline Performance Analysis	PASS
Test 6.2:	PASS
Test 6.3: Packet Error Rate Estimation	PASS
Test 6.4: Packet Loss/Stress Test	PASS

Notes

Conformance Test Results	
Test Information	Test Result
Test 1.1: <i>Purpose:</i> To verify that a host can pass a random sampling of ONIE Compliance Environment tests.	N/A
Comments on Test Procedure	
The random sampling of tests from the ONIE Compliance Environment was not used.	
Comments on Test Results	
Additional Comments	
This test is only applicable to Hosts which have not performed ONIE compliance testing previously.	
Test Information	Test Result
Test 1.2: <i>Purpose:</i> To verify that a NOS can be successfully installed through ONIE.	PASS
Comments on Test Procedure	
This test was completed using the standard procedure as written in the Test Plan. The random sampling of tests from the ONIE Compliance Environment was not used.	
Comments on Test Results	
Part A: The DUT was able to install the NOS via ONIE. Part B: The DUT was able to uninstall the NOS via ONIE.	
Additional Comments	

Test Information	Test Result
Test 3.1.1: Return loss for 10G Passive Cable <i>Purpose:</i> To verify that the return loss of the DUT is within the conformance limits provided by SFF-8431 Appendix E, Table 37.	PASS
Comments on Test Procedure	
This test was completed using the standard procedure.	
Comments on Test Results	
The differential return loss observed did not violate the limits governed by SFF-8431 Appendix E.4, Table 37 for 10GBASE-CR passive cables: $11, \quad 22 \geq \left\{ \begin{array}{ll} 12 - 2\sqrt{}, & 0.01 \leq < 4.1 \\ 6.3 - 13 \log_{10} , & 4.1 \leq \leq 11.1 \end{array} \right\} (\quad)$	
Additional Comments	

Test Information	Test Result
Test 3.1.2: Insertion Loss for 10G Passive Cable <i>Purpose:</i> To verify that the insertion loss of the Cable under test is within the conformance limits provided by IEEE Std. 802.3-2012 Annex, Table 37.	PASS
Comments on Test Procedure	
This test was completed using the standard procedure.	
Comments on Test Results	
The insertion loss of the cable under test does not violate the requirements passive cable assemblies. $3 \leq 21, \quad 12 \leq 17.04, \quad 5.15625$	
Additional Comments	

Test Information	Test Result
<p>Test 5.1.1: Output Rise and Fall Times for 10G Host</p> <p><i>Purpose:</i> To verify that the Eye Mask Hit Ratio is within the conformance limits.</p>	<p>PASS</p>
<p>Comments on Test Procedure</p>	
<p>The test was completed with the standard procedure.</p>	
<p>Comments on Test Results</p>	
<p>The device under test exhibited the expected behavior.</p>	
<p>Additional Comments</p>	

Test Information	Test Result
<p>Test 5.1.2: Transmitter Eye Mask on 10G Host</p> <p><i>Purpose:</i> To verify that the Eye Mask Hit Ratio is within the conformance limits.</p>	<p>PASS</p>
<p>Comments on Test Procedure</p>	
<p>The test was completed with the standard procedure.</p>	
<p>Comments on Test Results</p>	
<p>The device under test exhibited the expected behavior.</p>	
<p>Additional Comments</p>	

Test Information	Test Result
Test 5.1.3: <i>Purpose:</i> To verify that the Total Jitter (TJ) is within the conformance limit.	PASS
Comments on Test Procedure	
The test was completed with the standard procedure.	
Comments on Test Results	
The device under test exhibited the expected behavior.	
Additional Comments	

Test Information	Test Result
Test 5.1.4: Input and Output Return Loss on 10G Host <i>Purpose:</i> To verify that the differential input and output return loss of the DUT is within conformance limits.	PASS
Comments on Test Procedure	
The test was completed with the standard procedure.	
Comments on Test Results	
The device under test exhibited the expected behavior.	
Additional Comments	
See Appendix B	

Interoperability Test Results	
Test Information	Test Result
Test 2.1: Physical Compatibility with Supporting Devices <i>Purpose:</i> To verify that the mechanical form factor is compatible with devices for interoperability purposes.	PASS
Comments on Test Procedure	
The test was completed with the standard procedure.	
Comments on Test Results	
Part A: The MUT/CUT was able to be inserted into the Host. Part B: This test is not applicable to Cable Assemblies. Part C: The MUT/CUT was able to be removed from the Host.	
Additional Comments	

Test Information	Test Result
Test 2.2: <i>Purpose:</i> To verify that the MUT/CUT is manageable via the Host complex.	PASS
Comments on Test Procedure	
The test was completed with the standard procedure.	
Comments on Test Results	
Part B: The EEPROM data of the MUT/CUT was readable. The serial number and vendor information extracted from the EEPROM data matches the serial number and vendor information of the part.	
Additional Comments	

Test Information	Test Result
Test 2.3: <i>Purpose:</i> To verify that the MUT/CUT (active optical cable only) supports diagnostic functions via the Host complex.	PASS
Comments on Test Procedure	
The test was completed with the standard procedure.	
Comments on Test Results	
Part A: The MUT/CUT supports diagnostic monitoring and the diagnostic information from the EEPROM was readable by the NOS.	
Additional Comments	

Test Information	Test Result
<p>Test 6.1: Establish Baseline Performance Analysis</p> <p><i>Purpose:</i> To establish a baseline performance analysis of the HUT.</p>	<p>PASS</p>
<p>Comments on Test Procedure</p>	
<p>This test was completed using a modified procedure. Because of a lack of 40G Golden Modules, the Host was baselined using each 40G MUT/CUT.</p>	
<p>Comments on Test Results</p>	
<p>The baseline performance of the Host was determined to be 90% line rate. All proceeding tests in Group 6 were conducted using this line rate.</p>	
<p>Additional Comments</p>	

Test Information	Test Result
<p>Test 6.2:</p> <p><i>Purpose:</i> To determine if the MUT/CUT, HUT and LP establish a link while varying the power up sequence.</p>	<p>PASS</p>
<p>Comments on Test Procedure</p>	
<p>This test was completed using the standard procedure.</p>	
<p>Comments on Test Results</p>	
<p>Part A: The Host and Link Partner were able to establish a valid link with this MUT/CUT while fully powered and operational. Part B: The Host and Link Partner were able to establish a valid link with this MUT/CUT when the Link Partner was powered on after the Host. Part C: The Host and Link Partner were able to establish a valid link with this MUT/CUT when the Host was powered on after the Link Partner.</p>	
<p>Additional Comments</p>	

Test Information	Test Result
<p>Test 6.3: Packet Error Rate Estimation</p> <p><i>Purpose:</i> To determine if a Host can exchange packets with a Module or Cable Assembly such that a bit error rate of 10^{-12} is achieved</p>	<p>PASS</p>
<p>Comments on Test Procedure</p>	
<p>This test was completed using the standard procedure.</p>	
<p>Comments on Test Results</p>	
<p>Part A: All 247,000,000 frames transmitted by TS1 were received by TS2. Part B: All 10,506,539,320 frames transmitted by TS1 were received by TS2.</p>	
<p>Additional Comments</p>	
<p></p>	


Test Information	Test Result
<p>Test 6.4: Packet Loss/Stress Test</p> <p><i>Purpose:</i> To verify that no obvious buffer management problems occur when directing a large volume of traffic at the Host and Module/Cable Assembly combination.</p>	<p>PASS</p>
<p>Comments on Test Procedure</p>	
<p>This test was completed using the standard procedure.</p>	
<p>Comments on Test Results</p>	
<p>Parts A-D: All 1,000,000,000 64-byte frames transmitted by TS1 were received by TS2. All 1,000,000,000 1518-byte frames transmitted by TS1 were received by TS2.</p>	
<p>Additional Comments</p>	
<p></p>	

Appendix A: EEPROM Data

```
10Gtek SFP/SFP+/SFP28 module
Part Number: CAB-10GSFP-P3M Serial Number: WTS31HA0058
10Gtek__WTS31HA0058_____EEPROMdecode_20180530194410.txt
SERIAL_ID Keys:
BR_MAX: 10300
BR_MIN: 10300
BR_NOMINAL: 10300
CABLE_SPEC: 0x0 0x0
CONNECTOR: 33
DATE_CODE: 171001
DIAGNOSTIC_MONITORING_TYPE: 0
ENCODING: 0
ENHANCED_OPTIONS: 0
EXT_IDENTIFIER: 4
IDENTIFIER: 3
LENGTH_50UM: 0
LENGTH_62_5UM: 0
LENGTH_OM3: 0
LENGTH_OM4_OR_CU: 128
LENGTH_SMF: 0
LENGTH_SMF_KM: 0
OPTIONS: 0x0 0x0
RATE_IDENTIFIER: 0
SFF_8472_COMPLIANCE: 8
TRANSCEIVER: 0x1 0x0 0x0 0x4 0x41 0x84 0x80 0xd5
TRANSCEIVER_EXT: 0
VENDOR_NAME: 10Gtek
VENDOR_OUI: 0x0 0x0 0x0
VENDOR_PN: CAB-10GSFP-P3M
VENDOR_REV: V01
VENDOR_SN: WTS31HA0058
WAVELENGTH: 0
Vendor Specific: 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0 0x0
0x0 0x
I2C Address A0h, bytes 0-127, in hex
0000x: 03042101 00000441 8480d500 67000000
0010x: 00000300 31304774 656b2020 20202020
0020x: 20202020 00000000 4341422d 31304753
0030x: 46502d50 334d2020 56303120 00000075
0040x: 00000000 57545333 31484130 30353820
0050x: 20202020 31373130 30312020 000008ca
0060x: 00000000 00000000 00000000 00000000
0070x: 00000000 00000000 00000000 00000000
I2C Address A2h, bytes 0-127, in hex
0000x: 00000000 00000000 00000000 00000000
0010x: 00000000 00000000 00000000 00000000
0020x: 00000000 00000000 00000000 00000000
0030x: 00000000 00000000 00000000 00000000
0040x: 00000000 00000000 00000000 00000000
0050x: 00000000 00000000 00000000 00000000
0060x: 00000000 00000000 00000000 00000000
```

0070x: 00000000 00000000 00000000 00000000

Appendix B: Pluggable Module / Cable Electrical Data



Appendix C: Host Electrical Data

